



# NetVanta 7060

## IP PBX

### Product Features

- Integrated IP PBX, voice mail, auto attendant and 24-port PoE switch
- Supports SIP trunking
- Supports SIP multisite networking
- IP PBX supports up to 100 SIP stations
- Supports ADTRAN IP 706/712 and certified Polycom® phones
- Supports PBX and key system modes
- Call queuing
- Transfer voicemail-to-email
- Supports Source and ANI Based Routing (SABR)
- SIP/PSTN Gateway
- Voice mail (3,000 messages, eight ports)
- Multi-level auto attendant
- Shared Line and Call Appearance
- Busy Lamp Field/Direct Station Select (BLF/DSS)
- Dial by name directory
- IP handset paging
- System scheduler
- Chassis includes:
  - 24 10/100 Ethernet (802.3af PoE) ports
  - Two analog station (FXS) ports
  - Two analog trunk (FXO) ports
  - Two 10/100/1000 Base-T ports
  - Two SFP slots
  - Two option module slots
  - One WAN Ethernet
- Multisite zone paging
- Native find-me/follow-me with simultaneous ring
- Wi-Fi® access controller for NetVanta Wireless Access Points (WAPs)
- DHCP Server
- Software music-on-hold
- Paging output, door relay
- Graphical User Interface (GUI)
- Industry-leading North American five-year warranty

The NetVanta® 7060 is an IP PBX for business locations of up to 100 employees and is designed to complement an existing VoIP-ready data network. The NetVanta 7060 includes SIP-based telephony features such as voice mail, multi-level auto attendant, caller ID name/number, classes of service, trunk groups, music-on-hold and overhead paging. Additional call options include call coverage lists, forwarding of calls to a cell phone, voice mail-to-email integration, as well as a 24-port fully powered PoE switch.

#### PBX and Key System

Shared Line Appearance (SLA), Shared Call Appearance (SCA) and Busy Lamp Field/Direct Station Select (DSS) are popular key system functions and are also supported in the NetVanta 7060. SLA enables one or more lines to appear on multiple phones within the system. For example, trunk lines such as Line 1, Line 2 and Line 3 could appear on each phone so users can “pick up Line 1,” or an incoming 1-800 line could appear on all phones as the sales line. BLF/DSS provides a visual indication of the status of phones configured in the system with a button to directly connect to stations.

#### SIP Trunking and Networking

The NetVanta 7060 supports SIP trunking which dynamically combines voice and data across a single SIP link to the service provider. The NetVanta 7060 also supports multi-site SIP networking for linking sites together to provide direct dial between sites and reduce inter-office communications costs.

#### Hardware and Software Platform

The NetVanta 7060 is powered by the ADTRAN® Operating System (AOS), and the integral switch provides 24 powered (802.3af) 10/100 Ethernet ports, with 802.1Q VLANs, 802.1p Class of Service, making the system fully ready and ideal for VoIP applications.

The NetVanta 7060 chassis includes two analog trunk and station interfaces and two expansion slots. For additional trunk and station connectivity, the NetVanta 7060 offers several Voice Interface Modules (VIMs). These include a four-port analog (FXO) trunk module, TI/PRI trunk module supporting voice or integrated voice and data, and a four-port analog (FXS) station module. A combination module which provides two analog stations and two analog trunks is also available.

A dual IP and TDM backplane architecture supports both IP and analog devices to eliminate common performance problems associated with converting TDM analog devices to IP. Fax and modem devices connect directly to the NetVanta 7060 and achieve full-rate performance across the PSTN.

Additional PoE switches can be uplinked with the NetVanta 7060 and expand the physical port count to 100.

#### Unified Communications

ADTRAN's Business Communications System provides a complete IP communications system with the NetVanta 7000 Series, hardware-based IP PBX bundled with the software-based Unified Communications solution with full unified messaging for voice, fax and email. This solution easily integrates with existing Microsoft Outlook® and Active Directory® platforms for click-to-dial, inbound/outbound IVR, conference server, fax server for desktop faxing, text-to-speech, find-me/follow-me, as well as a host of other features to enable business communications.

#### Integrated Functionality

The NetVanta 7060 adds the flexibility and functionality SME's gain value from. Call Queuing allows for a call center-like experience without the high cost. The find-me/follow-me function enables a mobile workforce with no drop-off in customer service and interaction. 911 support, for email notification to administrator of 911 being dialed, is available for no additional charge and builds peace of mind.



# NetVanta 7060

## ADTRAN, Inc.

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000  
256 963-8699 fax

### General Information

800 9ADTRAN  
info@adtran.com  
www.adtran.com

### Pre-Sales

#### Technical Support

800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

### Where to Buy

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

### Post-Sales

#### Technical Support

888 423-8726  
support@adtran.com  
www.adtran.com/support

### ACES Installation & Maintenance Service

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

### International Inquiries

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/international

### For the regional office nearest you, visit:

www.adtran.com/regional



TL19.1270



ADTRAN is an ISO 9001, ISO 14001 and a TL 9000 certified supplier.

61700706G1-8F June 2010  
Copyright © 2010 ADTRAN, Inc.  
All rights reserved.

## IP PBX

# Product Specifications

### IP PBX System Features

- Analog Trunks (Loop Start/Ground Start; FSK Capture of Caller ID name/number; two integral, 10 maximum)
- Analog Stations (Loop Start DTMF; 1500 feet over 26 AWG; two integral, 10 maximum)
- Auto-attendant (multilevel, eight-port)
- Shared Line Appearance (SLA)
- Shared Call Appearance
- Call queuing
- Paging through IP Phones
- Busy Lamp Field/Direct Station Select (BLF/DSS)
- System Scheduler (seven configurable modes: i.e., night, lunch, weekend)
- Public hold
- Find-Me/Follow-Me with simultaneous ring
- Call Detail Records
- Caller ID Name/Number Override (internal and external)
- Classes of Service
- Codec support includes G.711, G.729, G.722 (wideband)
- Configurable dial plan
- Software music-on-hold
- Door relay
- Door phone
- Email notification of voice mail message
- Global call coverage lists
- IP stations (100 maximum; SIP hardphone or softphone)
- Least-cost routing
- Operator groups
- Outgoing number substitution
- PRI or integrated voice/data PRI
- Personal phone manager Web page
- Ring groups (ring all, circular hunt group, UCD, executive)
- System Speed Dial
- T1 or integrated voice/data T1
- Trunk groups
- Variable length extension numbers (three-digit, four-digit)
- Voice mail (3,000 messages, eight ports)
- Virtual Extensions (20)
- Voice mail accounts (130)
- 24 DSP resources
- 64ms echo cancellation for VoIP calls

### IP Station Features

- Call Drop
- Call Forward (All, Busy, No Answer)
- Call Forward to Outside Line (cell phone)
- Call Hold
- Call logs
- Call Waiting
- Hands free intercom
- Do Not Disturb
- Headset jack
- Missed call indicator
- Music on Hold
- Overhead paging
- Redial
- Speakerphone
- Volume control
- Caller ID Name/Number
- Call Park
- Call Park Retrieve
- Call Transfer
- Conferencing (3-person)
- Emergency call override
- Message waiting light
- Multiple Call Appearances
- Mute
- Personal call routing (Call Coverages)

### Ethernet Switch Features

- 10/100Base-T (24)
- 10/100/1000Base-T (2)
- Two SFP slots
- Auto-Rate
- Auto-Duplex
- Auto-MDI/MDI-X
- 802.1d Spanning Tree
- 802.1p Class of Service aware/mark
- 802.1Q VLANs
- 802.3af Power over Ethernet (15.4 watts for each of the 24 ports)

### Management Features

- Command Line Interface (CLI)
- HTTP, HTTPS (Web browser)
- Telnet
- SSH

### Environment

- **Operating Temperature:** 0 to 50° C
- **Storage Temperature:** -20 to 70° C
- **Relative Humidity:** Up to 95%, non-condensing

### Physical

- **Chassis:** 1U, 19" rackmountable metal enclosure
- **Dimensions:** 1.7" H, 17.2" W, 12.8" D
- **Weight:** 11 lbs.
- **AC Power:** 100–250 VAC, 50/60 Hz
- **Power:** 450 watts

### Chassis Includes

- 24 10/100 Ethernet (802.3af PoE) ports
- 2 analog station (FXS) ports
- 2 analog trunk (FXO) ports
- 2 10/100/1000 Base-T ports
- 2 SFP slots
- 2 option module slots
- 1 WAN Ethernet for broadband Internet/IP access
- MoH or overhead paging ports
- Door relay

## Ordering Information

Equipment	Part #
<b>NetVanta 7060</b>	1700706G1
NVU BCS BNDL 100 LIC (UC Software Only)	1950101BSG1
NVU BCS BNDL w/7060 (UC Software and NetVanta 7060)	4200706G1#UC
<b>Voice Interface Modules (VIMs)</b>	
Analog 4-Port Station (FXS)	1200690E1
Analog 4-Port Trunk (FXO)	1202691G1
Analog 2-Port Trunk/2-Port Station	1202692G1
T1/PRI	1200695E1
<b>Fiber Expansion Modules</b>	
SFP Module, 1000Base-SXSFP	1200480E1
SFP Module, 1000Base-LXSFP	1200481E1

Copyright © 2008 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. Five-year warranty applies only to products sold in North America.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)